Technical Data Sheet

Order number: LG56279

Röhre Performance PRO Mediatube HI-CRI 1200 18-950-2000LM







Technical Details:

Luminous Flux:	2000 lm
LED Output:	18 W
Light Yield:	111 lm/W
Light Temperature:	5000 K
Light Color:	daylight
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<6
Beam Angle:	135 °
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 5630
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50Hz
Power Consumption:	18 W
Contains Driver:	✓
Power Factor (PF):	>0.94
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	26x1200 mm
Length of Tube:	1200 mm
Socket:	G13
Rotating Socket:	✓
IP Class:	20
Cover:	opal
Net Weight:	353 g
Type of Packaging:	box
Dimensions of Packaging:	1290xØ35
Weight incl. Packaging:	0.557 kg
Content Master Package:	25
Dimensions of Master Package:	1306x196x210 mm
Weight Master Package:	14,40 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808710

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de