


# Rectangula UP/Down 67-840-5000LM



## Technical Details:

|                              |                         |
|------------------------------|-------------------------|
| Luminous Flux:               | 5000 lm                 |
| LED Output:                  | 64 W                    |
| Light Yield:                 | 74 lm/W                 |
| Light Temperature:           | 4000 K                  |
| Light Color:                 | neutralwhite            |
| Color Rendering Index:       | ≥80 Ra                  |
| Color Consistency (SDCM):    | <4                      |
| Beam Angle:                  | 60 °                    |
| Light Emission:              |                         |
| LED-Chip Manufacturer:       | Samsung                 |
| LED-Chip:                    | SMD 5630                |
| Ignition Time:               | <0,5 s                  |
| Input Current:               | AC 220 - 240V, 50/60Hz  |
| Power Consumption:           | 68 W                    |
| Contains Driver:             | ✓                       |
| Driver Manufacturer:         | Osram                   |
| Power Factor (PF):           | >0.95                   |
| Input Driver:                | cable with flying leads |
| Output of Driver:            | DC 2x 48V, 700mA        |
| CC/CV:                       | CC                      |
| Input Lamp:                  | terminal                |
| Switching Cycles:            | >100.000                |
| Electrical Protection Class: | II                      |
| Ambient Temperature (TA):    | -20°C - 45°C            |

|                                                                             |                               |
|-----------------------------------------------------------------------------|-------------------------------|
| Dimensions:                                                                 | 1200x50x210 mm                |
| Mounting:                                                                   | Wand                          |
| Montageart:                                                                 | surface mounted               |
| IP Class:                                                                   | 20                            |
| Housing Color                                                               | silver                        |
| Housing Material:                                                           | aluminum                      |
| Coating:                                                                    | lacquered                     |
| Special Feature of Housing:                                                 | externally switchable up/down |
| Cover:                                                                      | opal                          |
| Net Weight:                                                                 | 5570 g                        |
| Type of Packaging:                                                          | box                           |
| Dimensions of Packaging:                                                    | 1300x260x250                  |
| Weight incl. Packaging:                                                     | 6.69 kg                       |
| Content Master Package:                                                     | 2                             |
| Dimensions of Master Package:                                               | 1300x250x270 mm               |
| Weight Master Package:                                                      | 7,8 kg                        |
| Product Line:                                                               | Premio Line                   |
| Warranty                                                                    | 3 years                       |
| Operating Hours:                                                            | 50.000 h L80/B20              |
| Disposal Obligation:                                                        | ✓                             |
| Customs Tariff Number:                                                      | 9405499090                    |
| Certifications                                                              | CE                            |
| Barcode:                                                                    | 4250557805887                 |
| Licht oben/unten separat schaltbar<br>über seitlichen integrierten Schalter |                               |

## Information and Downloads:



