

Integra R Recessed Spotlight 42-830-2760LM



Product information "Integra R Recessed Spotlight 42-830-2760LM"

LED Downlight

Litegear® Integra LED ceiling lights are able to replace traditional discharge bulbs from 50-70W. They are very energy friendly and can save up to 60% of energy costs. By the low power consumption and the high life it concerns a "Green Energy technology" product. Big heatsinks guarantee a low temperature on the LED Chip and have an excellent airstream for convectional cooling. Litegear LED downlights are available in different sizes and different colour temperatures. Due to it's extended lifespan you will save on maintenance cost as well.

Litegear® LED lights are developed in Germany and are manufactured under stady testing and in line with the European regulations.

We can offer dimmable drivers on demand.

applications:

shop and showroom

entrance halls



Technical Details:

Luminous Flux	2760 lm
Light Yield:	77 lm/W
Light Temperature:	3000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	36 W
Power Factor (PF):	0.9
Operating Hours:	>35.000 h L80/B20
Switching Cycles:	>50.000
Ignition Time:	<1 s
Ambient Temperature (TA):	-20°C - 40°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Pivot Range pan:	350 °
Pivot Range tilt:	30 °
Dimensions	170x187 mm
Cut-Out Dimensions	150 mm
Net Weight:	1063 g
Warranty	3 years

Information and Downloads:

