


Integra R Recessed Spotlight 42-830-2760LM



Technical Details:

Luminous Flux:	2760 lm
LED Output:	34 W
Light Yield:	77 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	45 °
Swappable Reflector:	✓
Light Emission:	downward
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 320mA, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 32-40V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	170x187 mm
Cut-Out Dimensions:	150 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range pan:	350 °
Pivot Range tilt:	30 °
IP Class:	20
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	powder-coated
Net Weight:	1063 g
Type of Packaging:	box
Dimensions of Packaging:	200x205x200
Weight incl. Packaging:	1.337 kg
Content Master Package:	6
Dimensions of Master Package:	625x220x410 mm
Weight Master Package:	8,50 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557806778

Information and Downloads:

