


Integra R Recessed Spotlight 50-840-4100LM



Technical Details:

Luminous Flux:	4100 lm
LED Output:	48 W
Light Yield:	79 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	45 °
Swappable Reflector:	✓
Light Emission:	upward
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	52 W
Contains Driver:	✓
Power Factor (PF):	>0.94
Output of Driver:	DC 30 - 40V, 1000mA
CC/CV:	CC
Switching Cycles:	>25.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	170x187 mm
Cut-Out Dimensions:	150 mm
Mounting:	Decke
IP Class:	20
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	1307 g
Type of Packaging:	box
Weight incl. Packaging:	1.772 kg
Warranty	3 years
Operating Hours:	30.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557802664

Information and Downloads:

