


Paraflecta Downlight 9-830-560LM



Technical Details:

Luminous Flux:	560 lm
LED Output:	8 W
Light Yield:	62 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	38 °
Light Emission:	downward
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	9 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 18 - 32V, 255mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	85x71 mm
Installation Depth:	71 mm
Cut-Out Dimensions:	72 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range pan:	360 °
Pivot Range tilt:	25 °
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	297 g
Type of Packaging:	box
Dimensions of Packaging:	130x95x115
Weight incl. Packaging:	0.354 kg
Content Master Package:	24
Dimensions of Master Package:	310x250x540 mm
Weight Master Package:	8,88 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	30.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557805290

Information and Downloads:

