


Nava Circle 100 6-840-520LM



Technical Details:

Luminous Flux:	520 lm
LED Output:	5 W
Light Yield:	87 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 5630
Ignition Time:	<0,5 s
Input Current:	AC 100 - 240V, 155mA, 50/60Hz
Power Consumption:	6 W
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.5
Input Driver:	cable with flying leads
Output of Driver:	DC 16-22V, 280mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	100x30 mm
Installation Depth:	27 mm
Cut-Out Dimensions:	75 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	glass rim
Cover:	frosted
Net Weight:	172 g
Type of Packaging:	box
Dimensions of Packaging:	140x115x70
Weight incl. Packaging:	0.236 kg
Content Master Package:	40
Dimensions of Master Package:	505 x 300 x375 mm
Weight Master Package:	9,82 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	30.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808215

Information and Downloads:



