



Fenestra Rectangle Eco Line 6030 40-840-2950LM



Technical Details:

Luminous Flux:	2950 lm
LED Output:	40 W
Light Yield:	74 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥85 Ra
Beam Angle:	110 °
Light Emission:	downward
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 5630
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	40 W
Contains Driver:	✓
Input Driver:	cable with flying leads
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>25.000
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	620x310x12 mm
Mounting:	Decke
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	3400 g
Type of Packaging:	box
Weight incl. Packaging:	2.702 kg
Warranty	2 years
Operating Hours:	30.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557803623

Information and Downloads:

