

Fina Circle 175-15-840-1020LM



Technical Details:

Luminous Flux:	1020 lm
LED Output:	15 W
Light Yield:	68 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
Ignition Time:	<0,5 s
Input Current:	AC 100 - 240V, 240mA, 50/60Hz
Power Consumption:	15 W
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 40-63V, 280mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	174x22 mm
Installation Depth:	22 mm
Cut-Out Dimensions:	158 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	394 g
Type of Packaging:	box
Weight incl. Packaging:	0.478 kg
Content Master Package:	30
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	35.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808291

Information and Downloads:



