

Performa 36/28-840-2550LM



Technical Details:

| | |
|---------------------------|------------------------|
| Luminous Flux: | 2550 lm |
| LED Output: | 26 W |
| Light Yield: | 91 lm/W |
| Light Temperature: | 4000 K |
| Light Color: | neutralwhite |
| Color Rendering Index: | ≥80 Ra |
| Beam Angle: | 36 ° |
| Swappable Reflector: | ✓ |
| LED-Chip Manufacturer: | Sharp |
| LED-Chip: | COB |
| Ignition Time: | <1 s |
| Input Current: | AC 220 - 240V, 50/60Hz |
| Power Consumption: | 28 W |
| Contains Driver: | ✓ |
| Power Factor (PF): | >0.9 |
| Input Driver: | lighting track |
| Output of Driver: | DC 36V, 700mA |
| Switching Cycles: | >50.000 |
| Ambient Temperature (TA): | -20°C - 45°C |

| | |
|-------------------------------|--------------------|
| Mounting: | Decke,Stromschiene |
| Pivot Range pan: | 355 ° |
| Pivot Range tilt: | 90 ° |
| IP Class: | 20 |
| Housing Color | silver |
| Housing Material: | aluminum |
| Coating: | powder-coated |
| Net Weight: | 1697 g |
| Type of Packaging: | box |
| Weight incl. Packaging: | 1.697 kg |
| Content Master Package: | 8 |
| Dimensions of Master Package: | 505x280x545 mm |
| Weight Master Package: | 14,2 kg |
| Product Line: | Premio Line |
| Warranty | 3 years |
| Operating Hours: | 50.000 h L70/B50 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405499090 |
| Certifications | CE |
| Barcode: | 4250557806327 |

Information and Downloads:

