Product Information

Order number: LG51073

Mean Well HBG-240H-48B





Product information "Mean Well HBG-240H-48B"

LED Power Supply

Mean Well HBG Series Single Output LED Switching Power Supply features universal AC input up to 305VAC, protections for short circuit, overload, over voltage, and over temperature, built-in active PFC function, and OCP point adjustments through the output cable or internal potentiometer. The Mean Well HBG-240-B Series 240W Single Output LED Switching Power Supply is IP67 designed for indoor or outdoor installations for LED lighting and moving sign applications.

Product Features:

• usable for all DC 48V Applications

Technical Details:

- Mains input: AC 90 305V, 47 63Hz
- Housing: Aluminium
- Output voltage: DC 48V, constant current
- Output voltage range: yes (DC 28,8- 48V)
- Rated power: 5A
- Output power: 240W
- Dimmable: yes via 1 10V (external voltage 1...10V DC, PWM, Potentiometer)
- Protection: short circuit, over load, over voltage
- Scope: LED strips and Illumination
- IP class: IP67 for indoor and outdoor use
- Safety standars: F, SELV, TÜV, CE
- Power Faktor: >0,95
- Efficiency: 93%
- Ambient temperature: -20° to 70°C
- Warranty: 5 years

Dimensions: external diameter 162 x 69 mm Weight: 2,1kg



Technical Details:

| Power Consumption: | 240 W |
|---------------------------|--------------|
| Power Factor (PF): | 0.95 |
| Operating Hours: | >50.000 h |
| Ambient Temperature (TA): | -20°C - 70°C |
| Housing Material: | aluminum |
| Housing Color | black |
| Dimensions | 192x96 mm |
| Net Weight: | 2100 g |
| Warranty | 5 years |

Information and Downloads:

