Technical Data Sheet

Order number: LG51123

Tridonic TALEXXconverter LCI 35W 350mA–900mA TOP SR

Technical Details:

Input Current:	AC 198 - 264V, 50/60Hz, DC 176 - 280V
Power Consumption:	42 W
Driver Manufacturer:	Tridonic
Power Factor (PF):	>0.97
Input Driver:	terminal
Output of Driver:	DC 17,5-90V, 350-900mA
CC/CV:	CC
Output Current Adjustable:	✓
Switching Cycles:	>100.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 55°C

Dimensions:	220x85x31 mm
IP Class:	20
Housing Color	white
Housing Material:	plastic
Net Weight:	238 g
Type of Packaging:	box
Weight incl. Packaging:	0.183 kg
Content Master Package:	10
Warranty	5 years
Operating Hours:	100.000 h
Disposal Obligation:	✓
Customs Tariff Number:	8504408390
Certifications	CE,ENEC,SELV
Connection:	Terminal
NOTWENDIGES ZUBEHÖR: Tridonic I-Select 2 Plug	
Ausgangsstromanpassung über Widerstandsplug	

Information and Downloads:

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de