
Technical Data Sheet


Order number: LG10968

Luna Plane IP66 Floodlight 120-840-16000LM









Technical Details:

Luminous Flux:	16000 lm
LED Output:	110 W
Light Yield:	133 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥82 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Light Emission:	
LED-Chip Manufacturer:	Edison
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	120 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.95
Input Driver:	cable with plug
Output of Driver:	DC 30 - 46V, 2000mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>100.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 55°C

Dimensions:	400x340x90 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	silver
Housing Material:	aluminum
Coating:	powder-coated
Cover:	prismatic
Net Weight:	7300 g
Type of Packaging:	box
Dimensions of Packaging:	485x415x135
Weight incl. Packaging:	8.37 kg
Content Master Package:	2
Dimensions of Master Package:	510x425x310 mm
Weight Master Package:	18 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	94054210
Certifications	CE,GS,ENEC,LM80
Barcode:	4250557809021
Meanwell Driver	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de