


Rectangula UP/Down 67-830-4500LM extern schaltbar



Technical Details:

Luminous Flux:	4500 lm
LED Output:	72 W
Light Yield:	66 lm/W
Light Temperature:	2900 K
Light Color:	warmwhite
Color Rendering Index:	≥83 Ra
Color Consistency (SDCM):	<3
Beam Angle:	60 °
Light Emission:	
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 5630
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	68 W
Contains Driver:	✓
Driver Manufacturer:	Osram
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 2x 48V, 700mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	1170x50x145 mm
Mounting:	Wand
Montageart:	surface mounted
IP Class:	20
Housing Color	silver
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	internal dual switch
Cover:	opal
Net Weight:	5750 g
Type of Packaging:	box
Dimensions of Packaging:	1300x60x150
Weight incl. Packaging:	7.425 kg
Content Master Package:	3
Dimensions of Master Package:	1330x270x370 mm
Weight Master Package:	18,30 kg
Product Line:	Premio Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557809410
Licht nach oben und unten von extern separat schaltbar	

Information and Downloads:



