
Technical Data Sheet

**Order number: LG51161**

# Tridonic TALEXXconverter LC 17W 250–700mA flexC SR EXC








## Technical Details:

| | |
|---|---|
| **Input Current:** | AC 198 - 264V, 94mA, 50/60Hz, DC 176 - 280V |
| **Power Consumption:** | 20 W |
| **Driver Manufacturer:** | Tridonic |
| **Power Factor (PF):** | >0.95 |
| **Input Driver:** | terminal |
| **Output of Driver:** | DC 15-50V, 250–700mA |
| **CC/CV:** | CC |
| **Output Current Adjustable:** | ✓ |
| **Switching Cycles:** | >100.000 |
| **Electrical Protection Class:** | II |
| **Compatible with Emergency Current:** | ✓ |
| **Loop-Through Cabling:** | ✓ |
| **Ambient Temperature (TA):** | -25°C - 50°C |

| | |
|---|---|
| **Dimensions:** | 200x70x31 mm |
| **IP Class:** | 20 |
| **Housing Color** | white |
| **Housing Material:** | Polycarbonat |
| **Special Feature of Housing:** | Through-wiring |
| **Net Weight:** | 186 g |
| **Type of Packaging:** | box |
| **Content Master Package:** | 10 |
| **Warranty** | 5 years |
| **Operating Hours:** | 100.000 h |
| **Disposal Obligation:** | ✓ |
| **Customs Tariff Number:** | 8504408390 |
| **Certifications** | CE,ENEC,SELV |
| **Barcode:** | 9006210525679 |
| **Connection:** | Terminal |
| Ausgangsstromanpassung über Widerstandsplug | |

Information and Downloads: