


# Röhre Performance PRO MKII 1500 23-840-3000LM



## Technical Details:

Luminous Flux:	3000 lm
LED Output:	23 W
Light Yield:	130 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	135 °
LED-Chip Manufacturer:	Epistar
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50Hz
Power Consumption:	23 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Switching Cycles:	>40.000
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	26x1500 mm
Length of Tube:	1500 mm
Socket:	G13
Rotating Socket:	✓
IP Class:	20
Cover:	frosted
Net Weight:	584 g
Type of Packaging:	box
Weight incl. Packaging:	0.587 kg
Content Master Package:	25
Dimensions of Master Package:	1650x200x210 mm
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557809700

Information and Downloads:

