

Tridonic TALEXXconverter LCA 10W 150-400mA dim one4all SR PRE



Product information "Tridonic TALEXXconverter LCA 10W 150-400mA dim one4all SR PRE"

Product description

- Independent dimmable LED Driver
- Constant current LED Driver
- Output current adjustable between 150 - 400 mA
- max. output power 10 W
- Nominal life-time up to 100,000 h
- Dimming range 1 to 100 %

Interface

- DALI DEVICE type 6
- DSI
- switchDIM (with memory function)
- corridorFUNCTION
- Input temperature sensor for LED control

Technical data

- Input voltage: AC 198 - 264V, 50 - 60Hz
- Max.output voltage: DC max. 60 V
- Output current:150 -400 mA
- Output power:10 W
- Casing: polycarbonate, white
- Dimmable: yes (Dali)
- Short-circuit, protection, overload protection
- Type of protection: IP20 for indoor
- Certificates: SELV, CE, RoHS, ENEC
- Power factor: >0,85
- Typ efficiency: 83%
- Ambient temperature: -25° bis 70°C
- 5-year guarantee
- Dimensions: 200x70x31 mm
- Weight: 0,136kg

Technical Details:

Power Consumption:	13 W
Power Factor (PF):	0.96
Operating Hours:	>100.000 h
Switching Cycles:	>100.000
Ambient Temperature (TA):	-25°C - 65°C
Housing Material:	plastic
Housing Color	white
Dimensions	200x70x31 mm
Net Weight:	203 g
Warranty	5 years

Information and Downloads:

