Technical Data Sheet


Order number: LG12229


Campa Flex Floodlight ASY150-840-20000LM











Technical Details:

Luminous Flux:	20000 lm
LED Output:	140 W
Light Yield:	133 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	130x60 °
Unified Glare Rating (UGR):	<20
Light Emission:	downward
LED-Chip Manufacturer:	Luxeon
LED-Chip:	SMD 5050
Ignition Time:	<0,5 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	150 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	275x320x215 mm
Mounting:	ceiling,wall,ground
Montageart:	surface mounted
IP Class:	66
IK Code:	10
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular, swivelling
Cover:	frosted
Net Weight:	4582 g
Type of Packaging:	box
Dimensions of Packaging:	365x205x315
Weight incl. Packaging:	5.05 kg
Content Master Package:	2
Dimensions of Master Package:	440x380x340 mm
Weight Master Package:	12,0 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,ENEC,LM80
Barcode:	4250557813370
Akzo Nobel Beschichtung	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

