

Campa Flex Floodlight FL150-840-20000LM



Product information "Campa Flex Floodlight FL150-840-20000LM"

LED Flood Light

Litegear® Campa Flex a stylish and modular LED outdoor floodlight. Available with different beam angels and power classes. Due to the use of alluminum dicast housing, inox screws and strong bracket it has a excellent corrosion resistance. Campa Flex is the perfect solution for use in factories, sport fileds, harbours, airports or for architectural applications. Because of it's weather sealed standard you can use it permanently outside in rough environment conditions. We use very efficient LED chips. SMD chips have a optimized heat dissipation to guarantee a long lifespan. The LED modules can be tilt adjusted . The LEDs are LM80 tested! Dimming function on option (1-10V, PWM, Dali).

Applications:

- sport field: Soccer, Tennis, Basketball, Golf
- harbour, airport, warehouse
- industrial and architectural applications

Technical Details:

- Safety Tests: EN 60598-1:2015, EN 60598-2-5:1998, ZEK01.4-08, EN 62493:2010, IEC 60598-2-5: 1998, IEC 60598-1:2008, AS/NZS 60598:2.5:2002, AS/NZS 60598.1:2013
- EMC Test: EN 55015:2013, EN 61547:2009, EN 61000-3-2:2006+A1: 2009+A2:2009, EN61000-3-3:2013

Photobiological Safety: EN62471: 2008



Technical Details:

Luminous Flux	20000 lm
Light Yield:	133 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	150 W
Power Factor (PF):	0.95
Operating Hours:	>100.000 h L70/B50
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	aluminum
Housing Color	black
Coating:	powder-coated
Dimensions	275x320x215 mm
Net Weight:	4600 g
Warranty	5 years

Information and Downloads:

