



Campa Flex Floodlight NB230-840-29400LM



Technical Details:

Luminous Flux:	29400 lm
LED Output:	230 W
Light Yield:	128 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	60 °
Unified Glare Rating (UGR):	<22
LED-Chip Manufacturer:	Lumileds
LED-Chip:	SMD 5050
Ignition Time:	<0,5 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	230 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.98
Input Driver:	cable with flying leads
Output of Driver:	DC 57-115V, 2100mA
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>50.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 55°C

Dimensions:	275x320x324 mm
Mounting:	ceiling,wall,ground
Montageart:	surface mounted
IP Class:	66
IK Code:	10
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular, swivelling
Cover:	Lens
Net Weight:	6040 g
Type of Packaging:	box
Dimensions of Packaging:	385x365x205
Weight incl. Packaging:	6.74 kg
Content Master Package:	2
Dimensions of Master Package:	405x390x440 mm
Weight Master Package:	15,4 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,ENEC,LM80
Barcode:	4250557810164
Akzo Nobel Beschichtung	

Information and Downloads:

