Technical Data Sheet

Order number: LG14220

New-Szena 40/35-830-3050LM BL



Technical Details:

Luminous Flux:	3050 lm
LED Output:	34 W
Light Yield:	87 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥85 Ra
Color Consistency (SDCM):	<3
Beam Angle:	40 °
Swappable Reflector:	✓
Light Emission:	downward
LED-Chip Manufacturer:	Citizen
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	35 W
Contains Driver:	✓
Driver Manufacturer:	Philips
Power Factor (PF):	>0.94
Input Driver:	lighting track
Output of Driver:	DC 32-42V, 900-1050mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	170x98x195 mm
Mounting:	Decke,Stromschiene
Montageart:	surface mounted
Pivot Range pan:	355 °
Pivot Range tilt:	90 °
IP Class:	20
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Cover:	clear
Net Weight:	1128 g
Type of Packaging:	box
Dimensions of Packaging:	210x120x220
Weight incl. Packaging:	1.262 kg
Content Master Package:	12
Dimensions of Master Package:	430x380x470 mm
Weight Master Package:	15,9 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557813950

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de