

Movara MKIII 70/38-940-3450LM WH



Product information "Movara MKIII 70/38-940-3450LM WH"

LED Tracklight

With the Movara MKIII Litegear® presents the update of the successful Movara series. Movara is characterized by a wide, symmetrical dispersion of 90 x 60° and is therefore suitable for illuminating walls, banners and shelves, for example in supermarkets. High-quality components such as ENEC certified electronic drivers with a 3-year manufacturer's warranty and COB chips from Bridelux ensure a long and reliable operating life of up to 35,000 hours L80. The Movara track spotlight is available in 3 light colors from warm white to neutral white and in 3 housing colors (black, white, silver). 3 phases can be selected and tapped via the trackrail adapter. The Tracklight can be rotated by 355 ° and swiveled by 90 ° for perfect positioning.

Technical Details:

Luminous Flux	3450 lm
Light Yield:	91 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥90 Ra
Color Consistency (SDCM):	3
Power Consumption:	38 W
Power Factor (PF):	0.98
Operating Hours:	>35.000 h L80/B10
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-10°C - 40°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Pivot Range pan:	355 °
Pivot Range tilt:	90 °
Dimensions	196x75x175 mm
Net Weight:	886 g
Warranty	3 years

Information and Downloads:

