

Technical Data Sheet

Order number: LG302338

Velostra Line 1500 60-840-7800LM







Technical Details:

Luminous Flux:	7800 lm
LED Output:	57 W
Light Yield:	130 lm/W
Light Temperature:	3750 K
Light Color:	neutralwhite
Color Rendering Index:	≥85 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Unified Glare Rating (UGR):	<26
Light Emission:	downward
LED-Chip Manufacturer:	Bridgelux
LED-Chip:	SMD 2835
Number of LED:	288
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 280mA, 50/60Hz
Power Consumption:	60 W
Contains Driver:	✓
Power Factor (PF):	>0.98
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Ambient Temperature (TA):	-10°C - 40°C

Dimensions:	1498x46,1x65,5 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
IK Code:	08
Housing Color	Alu
Housing Material:	aluminum
Special Feature of Housing:	PC Cover
Cover:	opal
Net Weight:	1603 g
Type of Packaging:	bag
Dimensions of Packaging:	1800x200x170
Weight incl. Packaging:	1.671 kg
Content Master Package:	6
Dimensions of Master Package:	1650x190x160 mm
Weight Master Package:	9,2 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,TÜV,LM80
Barcode:	4250557810485
Einfache und schnelle Montage	
3-phasig	
TüV geprüft durch Hersteller	

Information and Downloads: