
Product Information

Order number: LG58304

Morana 9-830-750LM IP65









Technical Details:

Luminous Flux	750 lm
Light Yield:	83 lm/W
Light Temperature:	3000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	1
Power Consumption:	9 W
Power Factor (PF):	0.95
Operating Hours:	>50.000 h L70/B20
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	aluminum
Housing Color	grey
Coating:	lacquered
Dimensions	265x90 mm
Net Weight:	1420 g
Warranty	3 years

Information and Downloads:

Product information "Morana 9-830-750LM IP65"

LED wall / ceiling lamp outdoor

The Litegear® Morana LED luminaire convinces with a timeless, round design. Morana is weatherproof IP65 and therefore suitable for permanent outdoor use. LED ceiling light has a sturdy aluminum housing with a milky plastic cover. Due to the milky diffuser, the light from the LEDs is distributed very evenly over a large area, ideal for illuminating entrances to houses, on facades, ceilings or under canopies. The ease of installation makes this product all the more versatile and enjoyable for any installer. Easy access to the LED board and to the terminal block. The surface-mounted luminaire has numerous rear cable entries in the middle or laterally at the edge. The Litegear® Morana Outdoor LED light can be easily mounted on almost any surface.

Long life up to 50,000 operating hours

On demand with microwave motion sensor available.

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de