



Morana 9-830-750LM IP65



Technical Details:

Luminous Flux:	750 lm
LED Output:	9 W
Light Yield:	83 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<1
Beam Angle:	110 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	9 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	265x90 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	grey
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	1420 g
Type of Packaging:	box
Dimensions of Packaging:	275x275x110
Weight incl. Packaging:	1.62 kg
Content Master Package:	10
Dimensions of Master Package:	520x290x575 mm
Weight Master Package:	16,7 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557811963

Information and Downloads:

