

Fina Circle UP 300 24-830-2040LM



Technical Details:

Luminous Flux:	2040 lm
LED Output:	22 W
Light Yield:	85 lm/W
Light Temperature:	3200 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	24 W
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 70V, 320-340mA
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>25.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	300x40 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
IK Code:	04
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	890 g
Type of Packaging:	box
Dimensions of Packaging:	310x310x40
Weight incl. Packaging:	1.03 kg
Content Master Package:	10
Dimensions of Master Package:	480 x 315 x 315 mm
Weight Master Package:	12,0 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	35.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808321

Information and Downloads:

