

Product Information

Order number: 7000538

BEG Bewegungsmelder PD3N-1C-AP-Micro







Product information "BEG Bewegungsmelder PD3N-1C-AP-Micro"

Part No. 92219

Product Information

- Remote control-capable ceiling motion detector with integrated acoustic sensor
- One channel for light switching
- Special optical system for detection of even the smallest movements
- Manual switching via push-button possible
- Additional functions can be set up using the optional remote control.
- Typical applications: monitoring of smaller areas like stairwells, private garages, galleries, wash rooms

Technical Data
Voltage:
110 - 240 V AC 50 / 60 Hz
Dimensions:
FC= Ø 83 x 81 mm
SM= Ø 106 x 53 mm
Power consumption:
approx. 0.5 W
Detection area:
vertical 360°
Range:
max. Ø 10 m across
max. Ø 6 m towards
max. Ø 4 m smaller movements
Monitored area (tangential movement):
79 m² / 2.5 m Mounting height
Mounting height
min./max./recommended:
Degree / class of protection:
FC= IP23 / Class II
SM= IP44 / Class II
Ambient temperature:
-25 °C to +50 °C
Housing:
Polycarbonate, UV-resistant
Channel 1 (lighting control) Switching power: 2300 W, cos φ = 1
1150 VA, cos φ = 0.5
300 W LED
Type of contact:

Technical Details:

Dimensions	106x53 mm
Net Weight:	275 g

Information and Downloads:

1x µ-contact, NO contact with tungsten pre-make contact
Follow-up time:
30 sec - 30 min, Pulse
Switch-on threshold:
10 - 2000 Lux