



Campa Flex Floodlight NSP230-840-31000LM



Technical Details:

Luminous Flux:	31000 lm
LED Output:	200 W
Light Yield:	150 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<3
Beam Angle:	15 °
Light Emission:	downward
LED-Chip Manufacturer:	Lumileds
LED-Chip:	SMD 5050
Ignition Time:	<0,5 s
Input Current:	AC 100 - 265V, 50/60Hz
Power Consumption:	206 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.98
Input Driver:	cable with flying leads
Output of Driver:	DC 57-115V, 2100mA
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 55°C

Dimensions:	275x320x324 mm
Mounting:	ceiling,wall,ground
Montageart:	surface mounted
IP Class:	66
IK Code:	10
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular, swivelling
Cover:	Lens
Net Weight:	6060 g
Type of Packaging:	box
Dimensions of Packaging:	385x365x205
Weight incl. Packaging:	6.76 kg
Content Master Package:	2
Dimensions of Master Package:	765x40x235 mm
Weight Master Package:	15,4 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,ENEC,LM80
Barcode:	4250557813394
Meanwell® ELG-C Driver	
Akzo Nobel Beschichtung	

Information and Downloads:

