



# Lunara ECO MKII 150-750-22000LM



## Technical Details:

|                                    |                         |
|------------------------------------|-------------------------|
| Luminous Flux:                     | 22000 lm                |
| LED Output:                        | 148 W                   |
| Light Yield:                       | 145 lm/W                |
| Light Temperature:                 | 5000 K                  |
| Light Color:                       | daylight                |
| Color Rendering Index:             | ≥70 Ra                  |
| Color Consistency (SDCM):          | <3                      |
| Beam Angle:                        | 120 °                   |
| Light Emission:                    |                         |
| LED-Chip Manufacturer:             | Lumileds                |
| LED-Chip:                          | SMD 3030                |
| Number of LED:                     | 210                     |
| Ignition Time:                     | <1 s                    |
| Power Consumption:                 | 152 W                   |
| Contains Driver:                   | ✓                       |
| Driver Manufacturer:               | Meanwell ELG            |
| Power Factor (PF):                 | >0.99                   |
| Input Driver:                      | cable with flying leads |
| CC/CV:                             | CC+CV                   |
| Input Lamp:                        | cable with flying leads |
| Switching Cycles:                  | >100.000                |
| Electrical Protection Class:       | I                       |
| Compatible with Emergency Current: | ✓                       |
| Ambient Temperature (TA):          | -20°C - 45°C            |
| Storage Temperature:               | -40°C - 60°C            |

|                                        |                     |
|----------------------------------------|---------------------|
| Dimensions:                            | 440x337x63 mm       |
| Mounting:                              | ceiling,wall,ground |
| Montageart:                            | surface mounted     |
| Pivot Range tilt:                      | 90 °                |
| IP Class:                              | 65                  |
| IK Code:                               | 08                  |
| Housing Color                          | black               |
| Housing Material:                      | aluminum            |
| Coating:                               | powder-coated       |
| Cover:                                 | clear               |
| Net Weight:                            | 4537 g              |
| Type of Packaging:                     | box                 |
| Dimensions of Packaging:               | 500x420x142         |
| Weight incl. Packaging:                | 5.93 kg             |
| Content Master Package:                | 1                   |
| Dimensions of Master Package:          | 500x420x142 mm      |
| Weight Master Package:                 | 5,9 kg              |
| Product Line:                          | Essential Line      |
| Warranty                               | 3 years             |
| Operating Hours:                       | 50.000 h L80/B20    |
| Disposal Obligation:                   | ✓                   |
| Customs Tariff Number:                 | 94054239            |
| Certifications                         | CE,LM80             |
| Barcode:                               | 4250557811567       |
| High System Efficiency: 130 Lumen/Watt |                     |
| inkl. 80cm Kabel                       |                     |
| inkl. 80cm cable                       |                     |

## Information and Downloads:



