Product Information

Order number: LG60009

Emergy Brick 3-860-150lm SC WH









Product information "Emergy Brick 3-860-150lm SC WH"

LED escape route light with self test fuction

Emergency light with single battery supply for escape route lighting. 3 hours emergency lighting with NI-CD battery.1500mA, 3.6V. Can also be used as escape route pictogram light. Pictogram with cutable directional arrow is enclosed. Good brightness and wide dispersion. LED light source with long life up to 40,000 hours. LED status display via green status LED. Nice, rectangular water- and dustproof IP65 body made of plastic. Permanent phase monitoring. Emergency battery operation: 3 hours.
Inkl. 4 exit direction signs: arrow left, right, up

- Operating device: emergency / mains: electronic ballast
- Beam angle: symmetrical> 120 °
- LED: 3W
- Luminous flux: typ. 150 lumens
- Incl. pictogram with cutable directional arrow and person symbol
- Dimensions: see drawing

Technical Details:

Luminous Flux	150 lm
Light Yield:	50 lm/W
Light Temperature:	6000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	6
Power Consumption:	3 W
Power Factor (PF):	0.75
Operating Hours:	>50.000 h L70/B50
Switching Cycles:	>50.000
Ignition Time:	<1 s
Ambient Temperature (TA):	0°C - 40°C
Housing Material:	Polycarbonat
Housing Color	white
Dimensions	352x110x60 mm
Net Weight:	480 g
Warranty	3 years

Information and Downloads: