


Emergy Brick 3-860-150lm SC WH



Technical Details:

Luminous Flux:	150 lm
LED Output:	3 W
Light Yield:	50 lm/W
Light Temperature:	6000 K
Light Color:	daylight
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 2835
Number of LED:	16
Ignition Time:	<1 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	3 W
Contains Driver:	✓
Power Factor (PF):	>0.5
Input Driver:	terminal
Input Lamp:	terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	0°C - 40°C
Storage Temperature:	0°C - 40°C

Dimensions:	350x110x60 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	08
Housing Color	white
Housing Material:	Polycarbonat
Cover:	clear
Net Weight:	613 g
Luminaire Type:	Rettingszeichenleuchte
Viewing Distance EN1838:	≥18 m
Included Signs:	Pfeil links rechts oben unten
Testing Facility:	automatischer Selbsttest
Battery Warranty:	2
Discharge Duration:	≥3 h
Battery Type:	NiCd
Battery Current:	1500 mA
Battery Charge Duration:	12 h
Initial Charge Duration:	24 h
Charging Power Consumption:	6 W
Battery Cell Quantity	1
Luminous Flux in Battery Mode:	135 lm
Standards for emergency luminaires:	DIN EN 60598-2-22, DIN EN 62034: 2012, Zeichen nach ISO 7010, Anforderung nach DIN EN 50172
Type of Packaging:	box
Dimensions of Packaging:	120x65x360
Weight incl. Packaging:	0.692 kg
Content Master Package:	12

Information and Downloads:



Weight Master Package:	9 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405423100
Certifications	CE
Barcode:	4250557817781
inkl. Batterie Accupack	
Autom.Dauertest jährlich, Funktionstest wöchentl.	
optional ist ein Deckeneinbaurahmen erhältlich	