

Exita Swing 3-860-45lm SC WH



Product information "Exita Swing 3-860-45lm SC WH"

LED emergency exit light

Litegear Exita Swing: single-battery emergency light for escape route marking. Universal swivel mounting kit for wall and ceiling mounting. The luminaire can be used on one or two sides. Optionally, a mounting arm for side installation is available (see accessories). Flat, elegant acrylic LED pictogram surface. Over 60% power saving compared to conventional 8W versions with fluorescent tubes. The exit sign sheets are interchangeable and are fastened by push-button fasteners. Manual test function and green status LED display. Continuous operation via 230V mains voltage or battery emergency operation of up to 3 hours. Fast installation and easy battery change. Almost no maintenance cost due to LED technology! 3x pictograms for escape Arrow: "left/right/up" included.

Optionally, we offer additional escape route pictograms in a set.

- Material: polycarbonate and acrylic
- incl. 4 legends
- Swivel range: 90°
- Accupack included
- average battery life: 4 years max.
- viewing distance: 24 meters
- Overload and discharge protection
- Discharge current: 160mA
- Battery: 4,8v 600mA, NI-CD
- charging current: 30mA



Technical Details:

| | |
|-----------------------------|-------------------|
| Luminous Flux | 45 lm |
| Light Yield: | 15 lm/W |
| Light Temperature: | 6000 K |
| Color Rendering Index (CRI) | ≥80 Ra |
| Color Consistency (SDCM): | 6 |
| Power Consumption: | 3 W |
| Power Factor (PF): | 0.5 |
| Operating Hours: | >50.000 h L70/B50 |
| Switching Cycles: | >30.000 |
| Ignition Time: | <1 s |
| Ambient Temperature (TA): | 0°C - 40°C |
| Housing Material: | Polycarbonat |
| Housing Color | white |
| Pivot Range tilt: | 90 ° |
| Net Weight: | 939 g |
| Warranty | 3 years |

Information and Downloads:

