
Technical Data Sheet

Order number: LG60039

Exita Swing 3-860-45lm SC WH







Technical Details:

Luminous Flux:	45 lm
LED Output:	3 W
Light Yield:	15 lm/W
Light Temperature:	6000 K
Light Color:	cold white
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 2835
Number of LED:	16
Ignition Time:	<1 s
Input Current:	AC 220-240VV, 50/60Hz
Power Consumption:	3 W
Contains Driver:	✓
Power Factor (PF):	>0.5
Input Driver:	terminal
Input Lamp:	terminal
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	0°C - 40°C
Storage Temperature:	0°C - 40°C

Mounting:	ceiling,wall
Montageart:	surface mounted
Pivot Range tilt:	90 °
IP Class:	20
Housing Color	white
Housing Material:	Polycarbonat
Special Feature of Housing:	Attachment housing swivelling
Cover:	clear
Net Weight:	939 g
Luminaire Type:	Rettungszeichenleuchte
Viewing Distance EN1838:	≥24 m
Sign Visible from Both Sides:	
Included Signs:	Pfeil links rechts oben unten + white
Testing Facility:	automatischer Selbsttest
Battery Warranty:	2
Discharge Duration:	≥3 h
Battery Type:	NiCd
Battery Current:	900 mA
Battery Charge Duration:	24 h
Initial Charge Duration:	36 h
Charging Power Consumption:	5 W
Battery Cell Quantity	1
Luminous Flux in Battery Mode:	140 lm
Standards for emergency luminaires:	DIN EN 60598-2-22, DIN EN 62034: 2012, Zeichen nach ISO 7010, Anforderung nach DIN EN 50172
Type of Packaging:	box
Dimensions of Packaging:	335x45x244

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Content Master Package:	10
Dimensions of Master Package:	490x300x325 mm
Weight Master Package:	10,6 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557817835
Über- und Entladeschutz, greene Status LED, Taster	
autom. Selbsttest: 30s /Woche, Langzeit: 1 x year	
auto selftest: weekly 30s, long duration: 1 x year	
inkl. 4 Schilder	
incl. 4 legends	