

# Xona Nova MKII 1274 35-840-4600LM Emergency



## Technical Details:

|                                    |                                   |
|------------------------------------|-----------------------------------|
| Luminous Flux:                     | 4600 lm                           |
| LED Output:                        | 35 W                              |
| Light Yield:                       | 128 lm/W                          |
| Light Temperature:                 | 4000 K                            |
| Light Color:                       | neutralwhite                      |
| Color Rendering Index:             | ≥80 Ra                            |
| Color Consistency (SDCM):          | <4                                |
| Beam Angle:                        | 120 °                             |
| Light Emission:                    | downward                          |
| LED-Chip:                          | SMD 2835                          |
| Number of LED:                     | 144                               |
| Ignition Time:                     | <0,5 s                            |
| Input Current:                     | AC 220-240V, 50/60Hz, DC 180-240V |
| Power Consumption:                 | 36 W                              |
| Contains Driver:                   | ✓                                 |
| Power Factor (PF):                 | >0.93                             |
| Input Driver:                      | terminal                          |
| Input Lamp:                        | Terminal                          |
| Switching Cycles:                  | >35.000                           |
| Electrical Protection Class:       | I                                 |
| Compatible with Emergency Current: | ✓                                 |
| Ambient Temperature (TA):          | -20°C - 50°C                      |

|                                                |                       |
|------------------------------------------------|-----------------------|
| Dimensions:                                    | 1274x140x90 mm        |
| Mounting:                                      | ceiling,wall          |
| Montageart:                                    | surface mounted       |
| IP Class:                                      | 65                    |
| IK Code:                                       | 09                    |
| Housing Color                                  | grey                  |
| Housing Material:                              | Polycarbonat          |
| Special Feature of Housing:                    | Stainless steel clips |
| Cover:                                         | frosted               |
| Net Weight:                                    | 3131 g                |
| Type of Packaging:                             | box                   |
| Dimensions of Packaging:                       | 1270x145x100          |
| Weight incl. Packaging:                        | 3.587 kg              |
| Content Master Package:                        | 6                     |
| Dimensions of Master Package:                  | 1300x325x315 mm       |
| Weight Master Package:                         | 22,51 kg              |
| Product Line:                                  | Advance Line          |
| Warranty                                       | 5 years               |
| Operating Hours:                               | 50.000 h L70/B20      |
| Disposal Obligation:                           | ✓                     |
| Customs Tariff Number:                         | 9405499090            |
| Certifications                                 | CE,LM80               |
| Barcode:                                       | 4250557817958         |
| optional mit Bewegungsmelder                   |                       |
| on option with sensor                          |                       |
| Vergleichbare Helligkeit: wie 2 x 36W T8 Röhre |                       |
| same brightness as 2 x 36W T8 flourescent tube |                       |
| Emergency battery light function 3 hours 300lm |                       |

## Information and Downloads:

