Technical Data Sheet

Order number: LG30197

Xona Nova MKII 1574 57-840-7300LM

Technical Details:

Luminous Flux:	7300 lm
LED Output:	53 W
Light Yield:	128 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz, DC 180-240V
Power Consumption:	57 W
Contains Driver:	✓
Power Factor (PF):	>0.93
Input Driver:	terminal
Input Lamp:	Terminal
Switching Cycles:	>35.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓

Dimensions:	1574x140x90 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	09
Housing Color	grey
Housing Material:	Polycarbonat
Coating:	lacquered
Special Feature of Housing:	Stainless steel clips
Cover:	frosted
Net Weight:	3383 g
Type of Packaging:	box
Dimensions of Packaging:	1570x145x100
Weight incl. Packaging:	3.926 kg
Content Master Package:	4
Dimensions of Master Package:	1600x430x140 mm
Weight Master Package:	16,73 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557817989
optional mit Bewegungsmelder und Notstrombetrieb	
on option with Emergency light function and sensor	
Vergleichbare Helligkeit: wie 2 x 58W T8 Röhre	
same brightness as 2 x 58W T8 flourescent tube	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de