


Emergency Plane Mini 1,5-840-150lm SC WH asym. Corridor Beam 2 x 45°



Technical Details:

| | |
|------------------------------|-----------------------|
| Luminous Flux: | 150 lm |
| LED Output: | 1.5 W |
| Light Yield: | 100 lm/W |
| Light Temperature: | 4000 K |
| Light Color: | neutralwhite |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <6 |
| Beam Angle: | 2x45 ° |
| Light Emission: | downward |
| LED-Chip Manufacturer: | Tiandian |
| LED-Chip: | SMD 5050 |
| Number of LED: | 1 |
| Ignition Time: | <1 s |
| Input Current: | AC 220-240VV, 50/60Hz |
| Power Consumption: | 2 W |
| Contains Driver: | ✓ |
| Power Factor (PF): | >0.5 |
| Input Driver: | terminal |
| CC/CV: | CC |
| Input Lamp: | terminal |
| Switching Cycles: | >50.000 |
| Electrical Protection Class: | II |
| Ambient Temperature (TA): | 0°C - 40°C |
| Storage Temperature: | 0°C - 50°C |

| | |
|-------------------------------------|--|
| Dimensions: | 45x27 mm |
| Installation Depth: | 25 mm |
| Cut-Out Dimensions: | 35 mm |
| Mounting: | Decke |
| Montageart: | recessed |
| IP Class: | 20 |
| IK Code: | 06 |
| Housing Color | white |
| Housing Material: | Polycarbonat |
| Special Feature of Housing: | Luminaire IP54 room side |
| Cover: | Lens |
| Net Weight: | 149 g |
| Luminaire Type: | Fluchtwegleuchtung |
| Testing Facility: | automatischer Selbsttest |
| Battery Warranty: | 3 |
| Discharge Duration: | ≥3 h |
| Battery Type: | Li-Ion |
| Battery Current: | 5000 mA |
| Battery Charge Duration: | 8 h |
| Initial Charge Duration: | 16 h |
| Charging Power Consumption: | 6 W |
| Battery Cell Quantity | 1 |
| Luminous Flux in Battery Mode: | 170 lm |
| Standards for emergency luminaires: | DIN EN 60598-2-22, DIN EN 62034: 2012, Anforderung nach DIN EN 50172 |
| Certified By: | LIA |
| Type of Packaging: | box |
| Dimensions of Packaging: | 242x95x30 |

Information and Downloads:



| | |
|--|------------------|
| Content Master Package: | 60 |
| Dimensions of Master Package: | 498x318x315 mm |
| Weight Master Package: | 13,20 kg |
| Product Line: | Essential Line |
| Warranty | 5 years |
| Operating Hours: | 50.000 h L70/B20 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405499090 |
| Certifications | CE,TÜV,LM80 |
| Barcode: | 4260733770090 |
| Über- und Entladeschutz, greene/rede Status LED | |
| gewinkelter Treiber/angled driver | |
| Selbsttest: 30s/Woche, Dauertest: 1xyear | |
| selftest: 30s/week, full duartion test: 1 x year | |
| IR Empfänger für Fernbedienung | |