


Quadura PRO Square 62-29-840-4000LM WH



Technical Details:

Luminous Flux:	4000 lm
LED Output:	28 W
Light Yield:	138 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	95 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Juwei
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200 - 240V, 50/60Hz
Power Consumption:	29 W
Contains Driver:	✓
Driver Manufacturer:	Tridonic
Power Factor (PF):	>0.98
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 60°C

Dimensions:	620x620x26,5 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20
IK Code:	06
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	powder-coated
Special Feature of Housing:	Seilabhängung möglich
Cover:	Lens
Net Weight:	6040 g
Type of Packaging:	box
Dimensions of Packaging:	715x75x715
Weight incl. Packaging:	6.86 kg
Content Master Package:	1
Dimensions of Master Package:	715x75x715 mm
Weight Master Package:	6,86 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L90/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80,D
Barcode:	4250557817927
Elegante Rastereinlegeleuchte	
optional auch dimmbare Treiber erhältlich	
Mittels Seilset auch abgehängt zu montieren	
Optional auch Batterie Notstrommodul lieferbar	

Information and Downloads:

