

IRA-L 22-840-1980LM-IP44



Technical Details:

Luminous Flux:	1980 lm
LED Output:	21 W
Light Yield:	90 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD
Ignition Time:	<1 s
Input Current:	AC 200 - 240V, 50/60Hz
Power Consumption:	22 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 50°C

Dimensions:	410x103 mm
Mounting:	ceiling,wall
IP Class:	44
Housing Color	white
Housing Material:	steel
Coating:	powder-coated
Cover:	opal
Net Weight:	807 g
Type of Packaging:	box
Dimensions of Packaging:	450x450x115
Weight incl. Packaging:	1.234 kg
Content Master Package:	5
Dimensions of Master Package:	600x470x475 mm
Weight Master Package:	7,29 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557818382
IP44 raumseits/room side	
weiche, gleichmäßige Ausleuchtung	

Information and Downloads:

