
Technical Data Sheet

Order number: LG14329

Vivra Disk 61-840-40-4300LM-TD-DIM







Technical Details:

Luminous Flux:	4300 lm
LED Output:	38 W
Light Yield:	113 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	
Dimmable:	✓
Method of Dimming:	"Triac Phasenan-/abschnitt"
LED-Chip:	SMD
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	38 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 27-45V, 1050mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 50°C

Dimensions:	610x15 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	Treiber in Halterung
Cover:	prismatic
Net Weight:	3642 g
Type of Packaging:	box
Dimensions of Packaging:	660x62x810
Weight incl. Packaging:	4.455 kg
Content Master Package:	4
Dimensions of Master Package:	835x68x273 mm
Weight Master Package:	19,55 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,LM80
Barcode:	4250557818344
70% direkte und 30% indirekt Lichtverteilung	
70% direct and 30% indirect light distribution	
Pendelleuchte inkl. Stahlseilset und Baldachin	
suspendet luminaire with steel wire set	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

