


# Vivra Disk 61-840-40-4300LM-TD-DIM



## Technical Details:

|                              |                           |
|------------------------------|---------------------------|
| Luminous Flux:               | 4300 lm                   |
| LED Output:                  | 38 W                      |
| Light Yield:                 | 113 lm/W                  |
| Light Temperature:           | 4000 K                    |
| Light Color:                 | neutralwhite              |
| Color Rendering Index:       | ≥80 Ra                    |
| Color Consistency (SDCM):    | <4                        |
| Beam Angle:                  | 90 °                      |
| Unified Glare Rating (UGR):  | <19                       |
| Light Emission:              |                           |
| Dimmable:                    | ✓                         |
| Method of Dimming:           | "Triac Phasen-/abschnitt" |
| LED-Chip:                    | SMD                       |
| Ignition Time:               | <0,5 s                    |
| Input Current:               | AC 200-240V, 50/60Hz      |
| Power Consumption:           | 38 W                      |
| Contains Driver:             | ✓                         |
| Power Factor (PF):           | >0.95                     |
| Input Driver:                | terminal                  |
| Output of Driver:            | DC 27-45V, 1050mA         |
| CC/CV:                       | CC                        |
| Input Lamp:                  | terminal                  |
| Switching Cycles:            | >50.000                   |
| Electrical Protection Class: | II                        |
| Ambient Temperature (TA):    | -20°C - 40°C              |
| Storage Temperature:         | -20°C - 50°C              |

|                                                |                      |
|------------------------------------------------|----------------------|
| Dimensions:                                    | 610x15 mm            |
| Mounting:                                      | Decke                |
| Montageart:                                    | surface mounted      |
| IP Class:                                      | 20                   |
| Housing Color                                  | white                |
| Housing Material:                              | aluminum             |
| Coating:                                       | lacquered            |
| Special Feature of Housing:                    | Treiber in Halterung |
| Cover:                                         | prismatic            |
| Net Weight:                                    | 3642 g               |
| Type of Packaging:                             | box                  |
| Dimensions of Packaging:                       | 660x62x810           |
| Weight incl. Packaging:                        | 4.455 kg             |
| Content Master Package:                        | 4                    |
| Dimensions of Master Package:                  | 835x68x273 mm        |
| Weight Master Package:                         | 19,55 kg             |
| Product Line:                                  | Advance Line         |
| Warranty                                       | 3 years              |
| Operating Hours:                               | 50.000 h L80/B20     |
| Disposal Obligation:                           | ✓                    |
| Customs Tariff Number:                         | 9405499090           |
| Certifications                                 | CE,LM80              |
| Barcode:                                       | 4250557818344        |
| 70% direkte und 30% indirekt Lichtverteilung   |                      |
| 70% direct and 30% indirect light distribution |                      |
| Pendelleuchte inkl. Stahlseilset und Baldachin |                      |
| suspendet luminaire with steel wire set        |                      |

Information and Downloads:

