


DURATA LINE 30-840-3600LM WFL



Technical Details:

Luminous Flux:	3600 lm
LED Output:	29 W
Light Yield:	120 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	100 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	30 W
Driver Manufacturer:	Boke
Input Driver:	plug connector
Output of Driver:	DC 38V, 800mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1550x50x95 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular
Cover:	frosted
Net Weight:	2765 g
Type of Packaging:	box
Dimensions of Packaging:	1560x60x105
Weight incl. Packaging:	2.995 kg
Content Master Package:	8
Dimensions of Master Package:	1580x265x245 mm
Weight Master Package:	25,6 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405219090
Certifications	CE
Barcode:	4250557819075
Elegante, modulare Lichtlinienleuchte für Büros	
optional auch dimmbare Treiber erhältlich	
optional 5 unterschiedliche LED-Optiken lieferbar	
Ideal für Shop- oder Flurbeleuchtung	
1,5m Zuleitung 3 x ,075mm² black	

Information and Downloads:

