Technical Data Sheet

**Order number: LG14384W**

# DURATA LINE 30-840-2800LM FL






## Technical Details:

| | |
|---|---|
| **Luminous Flux:** | 2800 lm |
| **LED Output:** | 29 W |
| **Light Yield:** | 93 lm/W |
| **Light Temperature:** | 4000 K |
| **Light Color:** | neutralwhite |
| **Color Rendering Index:** | ≥80 Ra |
| **Color Consistency (SDCM):** | <4 |
| **Beam Angle:** | 70 ° |
| **Unified Glare Rating (UGR):** | <19 |
| **Light Emission:** | downward |
| **LED-Chip:** | SMD 2835 |
| **Ignition Time:** | <0,5 s |
| **Input Current:** | AC 200-240V, 50/60Hz |
| **Power Consumption:** | 30 W |
| **Driver Manufacturer:** | Boke |
| **Input Driver:** | plug connector |
| **Output of Driver:** | DC 38V, 800mA |
| **CC/CV:** | CC |
| **Input Lamp:** | plug connector |
| **Switching Cycles:** | >100.000 |
| **Electrical Protection Class:** | I |
| **Ambient Temperature (TA):** | -10°C - 40°C |
| **Storage Temperature:** | -20°C - 55°C |

| | |
|---|---|
| **Dimensions:** | 1550x50x95 mm |
| **Mounting:** | Decke |
| **Montageart:** | surface mounted |
| **IP Class:** | 20 |
| **Housing Color** | white |
| **Housing Material:** | aluminum |
| **Coating:** | powder-coated |
| **Special Feature of Housing:** | modular |
| **Cover:** | frost mit Raster |
| **Net Weight:** | 2810 g |
| **Type of Packaging:** | box |
| **Dimensions of Packaging:** | 1560x60x105 |
| **Weight incl. Packaging:** | 3.04 kg |
| **Content Master Package:** | 8 |
| **Dimensions of Master Package:** | 1580x265x245 mm |
| **Weight Master Package:** | 26,35 kg |
| **Product Line:** | Advance Line |
| **Warranty** | 5 years |
| **Operating Hours:** | 50.000 h L80/B20 |
| **Disposal Obligation:** | ✓ |
| **Customs Tariff Number:** | 9405499090 |
| **Certifications** | CE,D |
| **Barcode:** | 4250557819044 |
| Elegante, modulare Lichtlinienleuchte für Büros | |
| optional auch dimmbare Treiber erhältlich | |
| optional 5 unterschiedliche LED-Optiken lieferbar | |
| Für Bildschirmarbeitsplätze geeignet | |
| Zuleitung 1,5m white 3 x 0,75mm² | |

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de