


Cetara Office 12030 BAP 36-840-4100LM



Technical Details:

Luminous Flux:	4100 lm
Light Yield:	114 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 4014
Ignition Time:	<0,5 s
Power Consumption:	36 W
Output of Driver:	DC 32-42V, 500-1000mA
CC/CV:	CC
Input Lamp:	plug connector
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	1195x295x10 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (44 room side)
IK Code:	02
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	lacquered
Cover:	prismatic
Net Weight:	2099 g
Type of Packaging:	box
Dimensions of Packaging:	1295x320x40
Weight incl. Packaging:	2.58 kg
Content Master Package:	5
Dimensions of Master Package:	1265x370x405 mm
Weight Master Package:	18 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557819303
LED-Treiber nicht im Lieferumfang enthalten!	
without LED driver!	
Low UGR <19 BAP	
PMMA Diffusor	

Information and Downloads:

