

RETROVA SELECT 150 35/60-CCT-Select-8000LM



Technical Details:

Luminous Flux:	8000 lm
LED Output:	56 W
Light Yield:	133 lm/W
Light Temperature:	4000,5000,6000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	100 °
Unified Glare Rating (UGR):	<25
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	648
Ignition Time:	<0,5 s
Input Current:	AC 198 - 264V, 50/60Hz, DC 176 - 276V
Power Consumption:	Power Select (35, 40, 50, 60 W)
Contains Driver:	✓
Driver Manufacturer:	Osram
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 175V, 200, 250, 300, 350mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	1490x96x74 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	lichtgrey
Housing Material:	ABS
Special Feature of Housing:	schlagzäh
Cover:	prismatic
Net Weight:	1901 g
Type of Packaging:	box
Dimensions of Packaging:	1520x100x82
Weight incl. Packaging:	2.138 kg
Content Master Package:	8
Dimensions of Master Package:	1540x427x185 mm
Weight Master Package:	18,5 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE,D
Barcode:	4250557818948
Osram LED Treiber mit einstellbarem Ausgangsstrom:	
Leistung einstellbar: 35, 40, 50, 60W max. 142lm/W	
EVG: ENEC-10/VDE/EMC/EL/CE; geeignet für Notstrom	
Leuchte mit begrenzter Oberflächentemperatur "D"	
CCT Select: 4000K, 5000K, 6000K by switch	

Information and Downloads:

