



Cantana 9-830/840-800LM SENSOR IP66 IK10



Technical Details:

Luminous Flux:	800 lm
LED Output:	8 W
Light Yield:	89 lm/W
Light Temperature:	3000,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	110 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	88
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 60mA, 50/60Hz
Power Consumption:	Power Select (5,9 W)
Contains Driver:	✓
Power Factor (PF):	>0.8
Input Driver:	terminal
Output of Driver:	DC 23-38V, 130/220mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	270x74 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	66
IK Code:	10
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	shockproof
Cover:	opal
Net Weight:	1742 g
Type of Packaging:	box
Dimensions of Packaging:	280x280x86
Weight incl. Packaging:	1.93 kg
Content Master Package:	10
Dimensions of Master Package:	465x295x585 mm
Weight Master Package:	19,7 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557819556
Farbwahl/CCT select:	3000/4000 Kelvin
Leistungswahl/Power select:	5/9 Watt
integr. Microwave Bewegungssensor	
schlagfest	

Information and Downloads:

