Technical Data Sheet

Order number: LG32093

LITEGEAR
LED Lighting Solutions

Alwetra 500S Sensor Modul IP65/IK10, max. 6m hight









Technical Details:

Dimmable:	✓
Method of Dimming:	1-10V
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	1 W
Input Lamp:	plug connector
Switching Cycles:	>50.000
Ambient Temperature (TA):	-20°C - 50°C

Information and Downloads:

Dimensions:	500x85x72 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	white
Housing Material:	Aluminium/PC
Special Feature of Housing:	polycarbonate
Cover:	frosted
Net Weight:	970 g
Weight incl. Packaging:	0.97 kg
Product Line:	Advance Line
Warranty	2 years
Operating Hours:	25.000 h
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557818153
Maximale Montagehöhe: Decke 15m, Wand: 3m	
Erfassungsbereich max: Decke 12m, Wand 20m	
Stand-by time: 10s/1min/10min/30min/1h	
Hold time: 5s/30s/1min/5min/10min/20min/30min	
Stand-by Dim. Level: 10-50%	

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de