Product Information

Order number: LG32252

Modulux Linear LED- Modul 150-35/50-840-7500lm-WH





Technical Details:

Luminous Flux	7500 lm
Light Yield:	150 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	4
Power Consumption:	50 W
Power Factor (PF):	0.95
Operating Hours:	>50.000 h L80/B10
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Dimensions	1490x60x11 mm
Net Weight:	1150 g
Warranty	5 years

Information and Downloads:

Product information "Modulux Linear LED-Modul 150-35/50-840-7500lm-WH"

Linear LED tracklight for 3-phase trackrails

Elegant, flat LED luminaire with integrated 3-phase track adapter which is completely integrated in the standard track rails. Elegant, ultra flat appearance only 11mm high and 60mm wide. Available with symmetrical 60/90/120° or asymmetrical light dispersion 2 x 40° with multi-lens panel. Ideal for illuminating supermarket shelves, retail areas, exhibition halls, extremely high luminous flux up to 8000 lumens with only 50W consumption corresponding to up to 160 lumens / watt.

- Easy and fast installation using 3-phase trackrail adapters.
- 3 selectable power phases, compatible with all common track systems
- Adjustment output power: Adjustable LED driver 35, 40, 45, 50Watt
- Modular structure of the lens panel
- The individual modules can be seamlessly lined up. It creates the impression of a continuous line of light.
- Good heat dissipation and optimal light distribution
- Also available with dimmable Dali driver on request.
- Available in 2 housing colors: black, white optional also in silver (clarify minimum quantity beforehand)
- Long life LED technology: up to 50.000 hours L80 B10

- available in two lengths: 60cm and 150cm