


BREVIA SWING 5-927-930-370LM Triac Dim



Technical Details:

Luminous Flux:	370 lm
LED Output:	4.5 W
Light Yield:	74 lm/W
Light Color:	warmwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<4
Beam Angle:	36 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	"Triac Phasen-/abschnitt"
LED-Chip:	Bi-COLOR COB
Number of LED:	1
Ignition Time:	<0,5 s
Power Consumption:	5 W
Contains Driver:	✓
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminalbox
Switching Cycles:	>30.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-10°C - 35°C
Storage Temperature:	-20°C - 50°C

Dimensions:	82x28 mm
Installation Depth:	26 mm
Cut-Out Dimensions:	72-76 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range tilt:	10 °
IP Class:	20 (44 room side)
IK Code:	06
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Terminalbox
Cover:	Lens
Net Weight:	142 g
Type of Packaging:	box
Dimensions of Packaging:	110x95x50
Weight incl. Packaging:	0.163 kg
Content Master Package:	50
Dimensions of Master Package:	490x265x240 mm
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	25.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	94051190
Certifications	CE,D
Barcode:	4250557820132
integrierter Treiber + externes Anschlussterminal	
für 75mm Ausschnitt geeignet	
dimmbar mediums Phasen-/ -abschnitt Dimmer	
CCT select: 2700K/3000K	

Information and Downloads:



