

Campa Flex SF Floodlight NB450-757-65700LM



Technical Details:

Luminous Flux:	65700 lm
LED Output:	430 W
Light Yield:	146 lm/W
Light Temperature:	5700 K
Light Color:	daylight
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<3
Beam Angle:	60 °
Light Emission:	downward
LED-Chip Manufacturer:	Lumileds
LED-Chip:	SMD 5050
Ignition Time:	<0,5 s
Power Consumption:	450 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 55°C

Dimensions:	685x390x240 mm
Mounting:	Wand,Boden
Montageart:	surface mounted
IP Class:	66
IK Code:	10
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular, swivelling
Cover:	Lens
Net Weight:	17700 g
Type of Packaging:	box
Weight incl. Packaging:	19 kg
Content Master Package:	1
Dimensions of Master Package:	710x395x334 mm
Weight Master Package:	19 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405421000
Certifications	CE,ENEC,LM80
Barcode:	4250557820385
optional 1-10V dimmbar	
Akzo Nobel Beschichtung	
10KV surge predection	

Information and Downloads:

