

Fina Circle 200 15-840-1420LM



Product information "Fina Circle 200 15-840-1420LM"

Recessed LED luminaire

Litegear® Fina LED recessed flat luminaire panel with edge lighting technology for installation in ceilings or plasterboard walls. Easy mounting by snap-in holder. Very homogeneous light distribution and high brightness. Ideal for lighting of retail areas, lobbies, aisle or offices. Light with low glare. Power is supplied via an external power supply. Dimmable drivers on demand. Very stylish and time less design. Long lifespan and low power consumption. Only 12-20mm deep.

Fina Series can be ordered in different sizes and shapes: round or square. The cooling of the LEDs are embedded laterally over an aluminum housing. Litegear® luminaires are equipped with quality LED chips with good color rendering. Thus, the color of the illuminated products can be reproduced with almost natural quality.



Technical Details:

Luminous Flux	1400 lm
Light Yield:	93 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥80 Ra
Color Consistency (SDCM):	6
Power Consumption:	15 W
Power Factor (PF):	0.9
Operating Hours:	>35.000 h L70/B50
Switching Cycles:	>30.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 40°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Dimensions	200x22 mm
Cut-Out Dimensions	184 mm
Net Weight:	394 g
Warranty	2 years

Information and Downloads:

